

Cam Spray Model 2000QE Q Series Oil Fired Hot Water Pressure Washer

- Triplex plunger pump with ceramic plungers and stainless steel valves
- Adjustable pressure
- Adjustable thermostat
- Pressure pop-off
- Chemical injection
- Totally enclosed fan cooled motor (U.S. manufactured)
- Powder coated 1 1/2 inch steel tube frame with wand/hose rack (U.S. Manufactured)
- 13" tires
- Easily replaceable schedule 80 coil with stainless cold wrap (U.S. manufactured)
- Unit can be operated as either a cold water only or hot water unit
- Laser cut logo on frame; private label available
- Wet steam option available: Call for Pricing
- Look for optional accessories like the swivel hose reel (526496.KIT) that mounts to the frame
- Assembled in USA
- **All hot water machines must be properly vented if operated indoors**



Product Specifications:

- Operating Pressure in psi/bar : 2000 / 138
- Flow Rate in gpm/lpm : 4 / 15.2
- Horsepower : 5
- Voltage/Amperage/Phase : 230 Volt / 28 Amp / 1 ph
- 3 Phase option Available: Call for Pricing
- Power Cord : 35' with GFCI
- Maximum Pump Inlet Water Temperature : 140° F
- Pump Thermal Protection : Mechanical
- Hose Dimension : 50' x 3/8"
- Gun/Wand/Tip: Trigger gun/dual wand with side handle and soap tip, interchangeable tips in 0°, 15°, 25° and 40° pressure nozzles
- Burner Fuel Type : #1, #2 Diesel, Kerosene or JP8
- Burner Fuel Tank Capacity : 9 gallon
- CETL approved to UL 1776 and CSA C22.2 standards
- Product Dimension: 54" L x 32" W x 49" H
- Ship Weight : 595 lbs.

Cam Spray • 520 Brooks • Iowa Falls, IA 50126

Phone: 641-648-5011 • Toll Free: 800-648-5011 • Fax: 641-648-5013 • Email: sales@camspray.com